

Fox ESS EQ BATTERY STORAGE SYSTEM



HIGH VOLTAGE BATTERY FROM Fox ESS

The EQ is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 41.94 kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.

- 4.66kWh capacity
- Scalable to 41.94 kWh
- 90% Depth of Discharge
- Large temperature tolerance
- Easy installation
- CAN communication
- High voltage



**High
Voltage**



**Simple
Installation**



**High
Efficiency**



**Expandable
System**



**90%
DoD**

Fox ESS

EQ SERIES

EQ4800-L2/L3/L4/L5/L6/L7/L8/L9

MODEL	EQ4800 -L2	EQ4800 -L3	EQ4800 -L4	EQ4800 -L5	EQ4800 -L6	EQ4800 -L7	EQ4800 -L8	EQ4800 -L9
ELECTRICAL CHARACTERISTICS								
Battery Type	LiFePO4							
Battery Module	1*EQ4800-M 1*EQ4800-S	1*EQ4800-M 2*EQ4800-S	1*EQ4800-M 3*EQ4800-S	1*EQ4800-M 4*EQ4800-S	1*EQ4800-M 5*EQ4800-S	1*EQ4800-M 6*EQ4800-S	1*EQ4800-M 7*EQ4800-S	1*EQ4800-M 8*EQ4800-S
Nominal Voltage [V]	89.6	134.4	179.2	224	268.8	313.6	358.4	403.2
Nominal Energy [kWh]	9.32	13.98	18.64	23.3	27.96	32.61	37.27	41.93
Usable Energy [kWh] ¹⁾	8.38	12.58	16.77	20.97	25.16	29.34	33.54	37.73
Operating Voltage[V]	81.2 ~ 103.0	121.8 ~ 154.5	162.4 ~ 206.0	203.0 ~ 257.6	243.6 ~ 309.1	284.2 ~ 360.6	324.8 ~ 412.2	365.4 ~ 463.7
Normal capacity [Ah]	104							
Recommend Charge/Discharge Current [A]	30							
Max.Charge/Discharge Current [A] ²⁾	50							
Peak Discharge Current(60S) [A]	65							
Battery Pack Round-Trip Efficiency [%] ¹⁾	>95							
Depth Of Discharge [%]	90							
Cycle Life ¹⁾	≥6000							
Communication	CAN							
Display	EQ4800-S: LED*1, EQ4800-M: LED*6							
Scalability	Max. 9 Modules in Series							
OPERATING CONDITIONS								
Installation Location	Outdoor/ Indoor (Stand)							
Operating Temperature [°C]	Charge: 0 ~ 55 Discharge: -10 ~ 55							
Storage Temperature [°C]	-10 ~ 35							
Cooling method	Natural Convection							
Humidity [%]	5 ~ 95 (No Condensing)							
Altitude [m]	Max. 2,000							
MECHANICAL CHARACTERISTICS								
Dimensions (W*H*D) [mm]	570*386*380	570*524*380	570*662*380	570*800*380	570*938*380	570*1076*380	570*1214*380	570*1352*380
Weight [kg]	83.5	122.5	161.5	200.5	239.5	278.5	317.5	356.5
CERTIFICATES								
Safety	IEC 62619							
EMC	EN IEC 61000-6-1/2/3/4							
Transportation	UN38.3							
Ingress Protection	IP65							
WARRANTY								
Standard Warranty [year] ³⁾	10 ³⁾							

*1, @25°C, @70% SOH, @90% DOD, 0.3C charging/discharging.

*2, The current is affected by temperature ,cell voltage and SOC.

*3, Refer to FoxESS Battery Warranty Terms and Conditions.